

**FLEETWOOD FOLDING TRAILERS, INC.
INSTALLATION INSTRUCTIONS**

**1968T452
Revised June 2006**

DELUXE ADD-A-ROOM INSTALLATION INSTRUCTIONS

These instructions are for use on 2004 models, 2005 Destiny, Grand Tour, Highlander models, 2006 – 2007 Destiny, Americana, Highlander, and Element (except Neon) models:

This Kit Contains:

1	-	4724-794	Add-a-room bag
1	-		Add-a-room front
1	-		Add-a-room left side
1	-		Add-a-room right side
1	-		Rear skirt
1	-	4716-4011	Wheel well flap
8	-	4724A255	Plastic stakes
4	-	4720E402	Plastic lashing hooks
1	-	4351400005	Roll adhesive-backed Velcro
4	-	4733-413	¾" self-tapping Phillips head screws
16"	-	4753A863	Velstick
5	-	1103E101	5/8" stainless steel screws
2	-		Screen room adapters (short)
2	-	4730A354	Snap stud with screw (Taos and Laredo models only have one)
5	-	4733-411	Self-tapping screw (2006 models with steel body panels only)
2	-		Screen room adapter (long) 2007 to present Americana or Highlander

IMPORTANT NOTICE

These instructions are for the use of qualified individuals specifically trained and experienced in the installation of this type equipment and related system components. Installation and service personnel are required by some states to be licensed. Persons not qualified shall not attempt to install this equipment nor interpret these instructions.

PREPARING THE TRAILER FOR ADD-A-ROOM ATTACHMENT

1. Raise the trailer top to full height, pull out beds, attach bed support legs and stretch out canvas (not necessary to position canvas support rods).
2. Locate the two lashing hooks on the curbside rail next to the lift arms by aligning the hooks on the body rail with the canvas side zippers as shown in Figures 1 and 2. Pre-drill the holes with a 1/8" drill bit and attach with 3/4" self-tapping Phillips head screws provided.
3. Locate two additional lashing hooks along the bottom body panel edge. Place them so they are in direct alignment with the upper hooks installed in Step 2. Attach the hooks with the 3/4" self-tapping Phillips head screws provided. See Figures 1 and 2.